



TECHNICAL SPECIFICATIONS

Model	E-106	GH-06	GH-07	GH-1	GH-2	GH-3	GH-4
Excavator weight (t)	0,7 - 1,0	1,2 - 2,0	1,5 - 3,0	2,2 - 3,5	2,7 - 4,5	4 - 9	6 - 12
Operating weight* (kg)	62	127	138	221	268	391	634
Total length (mm)	872	1037	1088	1212	1291	1427	1690
Oil flow (l/min)	15 - 20	10 - 25	15 - 35	25 - 50	25 - 60	45 - 100	50 - 120
Blow frequency (bpm)	900 - 1200	480 - 1200	500 - 1200	550 - 1100	500 - 1200	500 - 1150	400 - 1000
Min. excavator pressure (MPa)	15 ~	17,5 ~	17,5 ~	17,5 ~	21 ~	17,5 ~	17,5 ~
Chisel diameter (mm)	41	42	47	57	66	76	86

Model	GH-6	GH-7	GH-9
Excavator weight (t)	12 - 18	14 - 21	17 - 24
Operating weight* (kg)	913	1345	1607
Total length (mm)	1931	2275	2395
Oil flow (l/min)	90 - 150	100 - 150	150 - 200
Blow frequency (bpm)	460 - 800	380 - 575	500 - 650
Min. excavator pressure (MPa)	21 ~	21 ~	21 ~
Chisel diameter (mm)	106	116	126

Model	GH-10	GH-12	GH-15	GH-18	GH-23	GH-30	GH-40
Excavator weight (t)	21 - 28	24 - 38	28 - 45	38 - 50	50 - 60	50 - 80	90 - 110
Operating weight* (kg)	1816	2310	2843	3292	4525	5450	7750
Total length (mm)	2575	2777	2988	3105	3325	3452	3867
Oil flow (l/min)	165 - 210	170 - 220	200 - 250	220 - 290	250 - 320	280 - 350	300 - 400
Blow frequency (bpm)	430 - 550	400 - 520	350 - 450	300 - 400	300 - 400	310 - 390	240 - 330
Min. excavator pressure (MPa)	21 ~	21 ~	21 ~	21 ~	21 ~	21 ~	21 ~
Chisel diameter (mm)	136	146	156	165	174	184	204

*Operating weight including standard top bracket

Technical specifications subject to change without prior notice