

T9 REV (FS-DF)

Per escavatori 5.0-12.0 ton / For excavators 5.0-12.0 ton

TRINCIATRICI IDRAULICHE
HYDRAULIC MULCHERS



T9 FS70 REV	
T9 FS90 REV	
T9 FS105 REV	



HF17 (FS)
Ø max 12 cm

T9 DF70 REV	
T9 DF90 REV	
T9 DF105 REV	



HF14
Ø max 25 cm

di serie
standard equipment



HF15
Ø max 20 cm



DF



FS



Modello Model	 (ton)	 (cm/inch)	 (LxAxH cm/inch)	 (kg/lbs)	 (cc)	 (L/min gal/min)	 bar/psi (min-max)		Rotore Rotor	
T9 FS70 REV	5.0-8.0	70 28	85x80x60 34x22x24	290 640	22-27-34- 44-51	40-50-60-80-100 11-14-16-22-28	200-220 2.900-3.200	3	4 file 4 lines	12
T9 FS90 REV	6.0-8.0	90 36	105x80x60 42x32x24	360 792	22-27-34- 44-51	40-50-60-80-100 11-14-16-22-28	200-220 2.900-3.200	3	elicoidale helical	18
T9 FS105 REV	6.0-12.0	105 42	125x80x60 50x32x24	400 882	27-34-44- 51	50-60-80-100 14-16-22-28	200-220 2.900-3.200	3	elicoidale helical	22
T9 DF70 REV	5.0-12.0	70 28	85x80x60 34x22x24	340 750	22-27-34- 44-51	40-50-60-80-100 11-14-16-22-28	200-220 2.900-3.200	3	elicoidale helical	21
T9 DF90 REV	6.0-12.0	90 36	105x80x60 42x32x24	400 882	27-34-44- 51	50-60-80-100 14-16-22-28	200-220 2.900-3.200	3	elicoidale helical	24
T9 DF105 REV	6.0-12.0	105 42	125x80x60 50x32x24	460 1.014	27-34-44- 51	50-60-80-100 14-16-22-28	200-220 2.900-3.200	3	elicoidale helical	30

Scelta motore idraulico a ingranaggi in ghisa Cast iron hydraulic gear motor range	 (ton)	5.0-6.0	6.0-7.0	7.0-8.0	8.0-10.0	10.0-12.0	Motore a pistoni a cilindrata variabile (accessorio) Variable displacement piston motor (accessory)	8.0-12.0
	 (cc)	22	27	34	43	51		32/64
	 (L/min - gal/min)	40 11	50 14	60 16	80 22	100 28		60/120 16/32

CARATTERISTICHE TECNICHE E DOTAZIONI STANDARD

- FS rotore forestale elicoidale con mazze a scomparsa.
- DF Rotore forestale a denti fissi.
- Trasmissione a cinghie trapezoidali dentate ad alte prestazioni.
- Cofanatura interna a doppia cassa con intercapedine.
- Protezione carter cinghie.
- Trinciatrice simmetrica per un taglio più veloce con la rotazione dell'escavatore.
- Bocche d'ingresso e d'uscita completamente identiche.
- Frontalini regolabili, apribili meccanicamente per una maggiore capacità di taglio.
- Slitte d'appoggio regolabili su 3 posizioni per variare l'altezza di taglio.
- Supporti rotore interni con labirinto per la protezione dei cuscinetti dalle impurità.
- Cuscinetti rotore a doppia corona di sfere orientabili di prima qualità.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione.
- Motore ad ingranaggi in ghisa.
- Protezioni antinfortunistiche con catene a norma CE.

TECHNICAL FEATURES AND STANDARD EQUIPMENT

- FS Helical forestal rotor with 360° rotating hammers.
- DF Forestal rotor, fixed teeth.
- Toothed high-performance V-belts transmission.
- Internally reinforced double-case body with interspace.
- Protective belts cover.
- Symmetric shearing head, for a faster cut with the rotation of the excavator.
- Input and output mouths completely identical, adjustable
- Adjustable hood, fully openable for higher cutting capacity.
- Side skids adjustable on 3 positions to change the height of the cut.
- Inside Rotor Supports with "labyrinth" for the protection of the bearings from the impurities.
- Double Row spherical adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Cast iron gear motor.
- Accident prevention chains protections according to EC directives.

ACCESSORI

- 1 - Attacco sella a perni 4.1-8.0 ton.
- 1.1 - Kit perni 4.1-8.0 ton.
- 2 - Attacco sella a perni 8.1-12.0 ton.
- 2.1 - Kit perni 8.1-12.0 ton.
- 3 - Kit tubi Lg. 2 metri MZ/FR/FS/DF.
- 4 - Rullo di appoggio.
- 5 - Supporto autolivellante (+40kg).
- 6 - Ralla girevole idraulica (senza autolivellante).
- 7 - Detrazione blocco valvole, solo anticavitazione.
- 8 - Motore a pistoni a cilindrata variabile (regolazione manuale).

ACCESSORIES

- 1 - Mounting hitch & pins 4.1-8.0 ton.
- 1.1 - Pins kit 4.1-8.0 ton.
- 2 - Mounting hitch & pins 8.1-12.0 ton.
- 2.1 - Pins kit 8.1-12.0 ton
- 3 - Hoses kit Lg. 2 meters MZ/FR/FS/DF.
- 4 - Feeler roller.
- 5 - Self-levelling support (+40kg).
- 6 - Hydraulic rotation device (not self-levelling support).
- 7 - Valves block deduction, only anticavitation.
- 8 - Variable displacement piston motor (manual adjustment).



1



4



5



6



8